iTcPower

empower your business

Diesel Inverter Generators

Silent, Twin-cylinder

DP14000SEi-T
DP16000SEi-T/DP20000SEi-T
DP22000SEi-T/DP25000SEi-T

www.itcpowergenertor.com

GENERATOR	DP14000SEi-T	DP16000SEi-T	DP20000SEi-T
Frecuency (Hz)	50/60	50/60	50/60
Rated Power	10kW/12.5kVA	12kW/15kVA	14kW/18kVA
Max. Power	11kW/13.8kVA	13kW/16.3kVA	15kW/20kVA
Voltage (V)	230/400	230/400	230/400
Current (A)	43/18	52/21.6	60.8/26
Plugs	63A&32A	63A&32A	63A&32A
Display	LED6	LED6	LED6
Fuel tank capacity (L)	46	46	46
Running time @75% load (H)	14.6	12.7	10.8
Sound level @ 7m (dBA)	-	-	-
Battery (V/Ah)	12V 6Ah	12V 6Ah	12V 6Ah
ENGINE	2V88	2V92	2V95
Engine type	Diesel	Diesel	Diesel
Power (hp)	18.7	21.4	25.2
Start	Electric	Electric	Electric
Displacement (CC)	912	997	1247
Oil Capacity (L)	2.8	3.5	3.5
ALTERNATOR	AL10-T	AL12-T	AL16-T
Power (Kw)	10	12	16
Power Factor	0.8	0.8	0.8
Voltage Regulation	PMG	PMG	PMG
DIMENSIONS & WEIGHT			
Net Weight (Kg)	260	290	300
Gross Weight (Kg)	280	310	320
Machine size (mm)	1030*680*880	1030*680*880	1030*680*880
Dimensions Package (mm)	1070*730*1150	1070*730*1150	1070*730*1150
FCL 20'/40'HQ	32/68	32/68	32/68

Specifications are subject to continuous product development

GENERATOR	DP22000SEi-T	DP25000SEi-T
Frecuency (Hz)	50/60	50/60
Rated Power	16kW/20kVA	18kW/22.5kVA
Max. Power	16.5kW/20.6kVA	18.5kW/23.1kVA
Voltage (V)	230/400	230/400
Current (A)	69.5/28.8	78.2/32.4
Plugs	63A&32A	63A&32A
Display	LED6	LED6
Fuel tank capacity (L)	46	46
Running time @75% load (H)	9.6	8.6
Sound level @ 7m (dBA)	-	-
Battery (V/Ah)	12V 6Ah	12V 6Ah
ENGINE	2V100	2V105
Engine type	Diesel	Diesel
Power (hp)	27.9	30.5
Start	Electric	Electric
Displacement (CC)	1382	1523
Oil Capacity (L)	3.5	3.5
ALTERNATOR	AL17-T	AL19-T
Power (Kw)	17	19
Power Factor	0.8	0.8
Voltage Regulation	PMG	PMG
DIMENSIONS & WEIGHT		
Net Weight (Kg)	305	305
Gross Weight (Kg)	325	325
Machine size (mm)	1050*660*900	1050*660*900
Dimensions Package (mm)	1090*700*1170	1090*700*1170
FCL 20'/40'HQ	32/68	32/68

Specifications are subject to continuous product development

Options

4Ah / 6Ah
Lithium Battery

Temperature
Sensor to stop

LED6
Voltage AC
Power output
Frequency / Current
Battery voltage
Working time

ATS/AUTO
module

NSK
bearing



EURO5
catalyst

Preheater

Standard packing

Accessories

ATS BOX

Remote controller